



# APC NetShelter SX, Server Rack Enclosure, 42U, White, 2258H x 750W x 1070D mm [TAA]

AR3150W

### **Overview**

Presentation	Wide enclosure with increased cable management options for high density server and networking applications. 42U height to easily roll through doorways.	
Lead time	Usually in Stock	

#### Main

Product or Component Type	Rack enclosure	
Number of rack unit	42U	
Provided equipment	Baying hardware Documentation CD	
	Key(s)	
	Keyed-alike doors and side panels	
	Leveling feet	
	Pre-installed casters	
	Side Panels	

## **Physical**

<del>-</del>		
Height	78.39 in (199.1 cm)	
Width	29.53 in (75 cm)	
Depth	42.13 in (107 cm)	
Net Weight	343.11 lb(US) (155.63 kg)	
Color	White	
Mounting preference	No preference	
Mounting Mode	Not rack-mountable	
Maximum Mounting Depth	36.02 in (91.49 cm)	
minimum mounting depth	10.31 in (26.19 cm)	
Rack Width	19"	
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 16 gauge rear door 18 gauge roof 18 gauge side panels	
Permanent permissible load	2250 lb(US) (1020.6 kg) dynamic 3750 lb(US) (1701.0 kg) static	

### **Conformance**

Standards	UL 2416
	UL 60950-1
	EIA-310E

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

# Ordering and shipping details

GTIN	731304320548
Country of origin	CN

## **Packing Units**

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	87.24 in (221.6 cm)
Package 1 Width	47.99 in (121.9 cm)
Package 1 Length	35.24 in (89.5 cm)
Package 1 Weight	370.002 lb(US) (167.83 kg)

## Compliance

Compliance	TAA
	BAA via COTS

# **Contractual warranty**

Warranty 5 year repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

<b>⊘</b> Environmental footprint		
Carbon footprint (kg CO2 eq, Total Life cycle)	509	

#### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration

#### **Use Again**

○ Repack and remanufacture		
Circul	arity Profile	End of Life Information
Take-	back	Yes

Image of product / Alternate images

### **Alternative**









## AR3150W



