



APC NetShelter Basic Rack PDU, 0U, 30A, 120V, 24 NEMA 5-20 outlet

AP7532

Product availability: Stock - Normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

| Color | Black |
|---------------------------|---|
| Product or Component Type | PDU |
| PDU Type | Basic |
| Cord length | 10 ft (3.05 m) |
| Number of cables | 1 |
| Provided Equipment | Installation guide Rack Mounting brackets Toolless Mounting Kit |

Complementary

| Input Voltage | 100 V 120 V |
|--------------------------|------------------------|
| Height | 63.74 in (161.9 cm) |
| Width | 2.20 in (5.6 cm) |
| Output Voltage | 120 V |
| Depth | 1.73 in (4.4 cm) |
| Net Weight | 12.28 lb(US) (5.57 kg) |
| Mounting Location | Side |
| Mounting preference | No preference |
| Input Plug Type | NEMA L5-30P |
| Mounting Mode | Rack-mounted |
| Rack units | 0U |
| Mounting position | Vertical |
| Line Rated Current | 24 A |
| Input current limits | 30 A |
| Load Capacity | 2880 VA |
| Input Frequency | 50/60 Hz |
| Outlet type and quantity | 24 NEMA 5-20R |

Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Product Certifications | cUL Listed UL Listed |
|---------------------------------------|--|
| Standards | CSA C22.2 No. 60950-1-03 UL 60950-1 |
| Ambient Air Temperature for Operation | 32113 °F (045 °C) |
| Relative Humidity | 095 % |
| Operating altitude | 010000 ft |
| Ambient Air Temperature for Storage | -13149 °F (-2565 °C) |
| Storage Relative Humidity | 095 % |
| Storage altitude | 050000 ft (015240 m) |

Ordering and shipping details

| Category | 80230-IG SEBA TO SEUSA | |
|-------------------|------------------------|--|
| Discount Schedule | BMS1 | |
| GTIN | 731304225522 | |
| Returnability | No | |
| Country of origin | PH | |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|------------------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 84.02 in (213.4 cm) |
| Package 1 Width | 5.00 in (12.7 cm) |
| Package 1 Length | 5.98 in (15.2 cm) |
| Package 1 Weight | 14.29 lb(US) (6.48 kg) |

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

| ☑ Environmental footprint | |
|--|-------------------------------|
| Carbon footprint (kg CO2 eq, Total Life cycle) | 137 |
| Environmental Disclosure | Product Environmental Profile |

Use Better

| Packaging made with recycled cardboard | Yes |
|--|---|
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant |
| REACh Regulation | REACh Declaration |
| Halogen content performance | Product contains halogen above thresholds |
| ᠃ Energy efficiency | |
| Optimized Energy Efficiency | Energy efficient product |

Use Again

| ○ Repack and remanufacture | |
|----------------------------|-------------------------|
| Circularity Profile | End of Life Information |
| Take-back | Yes |

Product data sheet

AP7532

Image of product / Alternate images

Alternative

