



APC Smart-UPS, Line Interactive, 3kVA, Rackmount 2U, 208V, 2x NEMA L6-20R outlets, SmartSlot, AVR, LCD

SMT3000RMT2U

Overview

Lead time Usually in Stock

Main

Product or Component Type Uninterruptible power supply (UPS)

Complementary

Communication port type SmartSlot

Batteries & Runtime

Run Time	View Runtime Graph ☐	
Efficiency	View Efficiency Graph ☐	
Battery Type	Lead-Acid battery	
Extendable Run Time	0	
Included Battery Modules	0	
Battery Slots Empty	0	
Typical recharge time	3 h	
RBC Quantity	1	
Battery life	35 year(s)	
Replacement battery	RBC43 ☐	
Battery Charge Power (Watts)	188 W rated	

General

Provided equipment	CD with software Documentation CD Rack mounting hardware Rack Mounting support rails	
	Smart UPS signalling RS-232 cable USB cable	
Number of power module	0	
Number of power module filled slots	0	
Number of power module free slots	0	
Redundant	No	

Physical

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Number of rack unit	2U	
Cable length	8 ft (2.4 m)	
Number of cables	1	
Height	3.39 in (8.6 cm)	
Width	18.90 in (48 cm)	
Depth	26.89 in (68.3 cm)	
Net Weight	97.62 lb(US) (44.28 kg)	
Mounting Location	Front	
Mounting preference	No preference	
Mounting Mode	Rack-mounted	
Two post mountable	0	
USB compatible	No	

Input

Main Input Voltage	208 V	
Input Connection Type	ype NEMA L6-20P	
Efficiency at full load	131268 V adjustable 141255 V	
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing	

Output

Main Output Voltage	208 V	
Kw Rating	2700 W	
rated power in VA	3000 VA	
output connection type	2 NEMA L6-20R	
Harmonic distortion	Less than 5%	
Maximum configurable power in VA	3000 VA	
Max Configurable Power (Watts)	2700 W	
Transfer Time	4ms typical : 8ms maximum	
Topology	Line Interactive	
Waveform Type	Sine wave	
Output frequency	50/60 Hz +/- 3 Hz sync to mains	

Conformance

Equipment protection policy Lifetime: \$150000

Environmental

Acoustic level	55 dBA	
Heat dissipation	348 Btu/h	
Operating altitude	010000 ft	
Ambient Air Temperature for Operation	32104 °F (040 °C)	
Ambient Air Temperature for Storage	5113 °F (-1545 °C)	

Storage altitude	050000 ft (015240 m)	
Relative Humidity	095 %	
Storage Relative Humidity	0. 95 %	

Communications & Management

control panel	Multi-function LCD status and control console
Free slots 1	
Alarm	Alarm when on hattery: distinctive low hattery alarm: configurable delays

Surge Protection and Filtering

Surge energy rating 320 J

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS	
GTIN	731304279556	
Returnability	No	
Country of origin	PH	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.00 in (25.4 cm)
Package 1 Width	38.58 in (98 cm)
Package 1 Length	23.62 in (60 cm)
Package 1 Weight	114.0 lb(US) (51.7 kg)

Contractual warranty

Warranty 3 years repair or replace (excluding battery) and 2 years for battery



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	2962
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Optimized Energy Efficiency	Energy efficient product

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes

Product data sheet SMT3000RMT2U

Image of product / Alternate images

Alternative

