

APC NetShelter Switched Rack PDU, 9K series, 0U, 11.5kW, 200-240V, 21 C13/C15 and 3 C19/ C21 outlets

APDU9981NA3

Overview

Lead time Usually in Stock

Main

Color	Black	
Product or Component Type	PDU	
PDU Type	Switched	
Cord length	6 ft (1.8 m)	
Number of cables	1	
Provided Equipment	Installation guide Rack Mounting brackets Safety guide	

Complementary

•		
Input Voltage	415 V 3 phase	
Height	70.51 in (179.1 cm)	
Width	2.17 in (5.5 cm)	
Output Voltage	208 V 240 V	
Depth	1.81 in (4.6 cm)	
Net Weight	15.4 lb(US) (7 kg)	
Mounting Location	Side	
Mounting preference	No preference	
Input Plug Type	IEC 60309 20 A 3P+N+PE	
Mounting Mode	Not rack-mountable	
Rack units	OU	
USB compatible	No	
Mounting position	Vertical	
Communication Port Protocol	SNMP Redfish	
Line Rated Current	16 A	
Max line current	20 A	
Input current limits	20 A	
Load Capacity	11500 VA	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Input Frequency	50/60 Hz
Outlet type and quantity	21C13/C15 3C19/C21
Communication Network Type	10/100/1000BASE-T

Environment

Product Certifications	cUL Listed FCC part 15 class A PSE	
Standards	UL 62368-1	
Ambient Air Temperature for Operation	23140 °F (-560 °C)	
Relative Humidity	595 %	
Operating altitude	010000 ft	
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)	
Storage Relative Humidity	595 %	
Storage altitude	050000 ft (015240 m)	

Ordering and shipping details

GTIN 731304404255

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	78.82 in (200.2 cm)	
Package 1 Width	4.49 in (11.4 cm)	
Package 1 Length	6.50 in (16.5 cm)	
Package 1 Weight	19.73 lb(US) (8.95 kg)	

Contractual warranty

Warranty 3 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	2814
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative



