



APC NetShelter Switched Rack PDU, 1U, 1.4kW, 120V, 15A, 8 NEMA 5-15R outlet

AP7900B

Product availability: Stock - Normally stocked in distribution facility

Overview

Presentation	This APC Switched Rack PDU power distribution unit has a wide range of standardized PDU features that increase network efficiency, manageability and functionality. The output and input connections are (8)5-15. Network management capabilities allow you to configure and manage rack PDUs from remote locations. It has has a local current monitoring display that gives a visible warning in case of an overload. The remote individual outlet control provides real-time monitoring of connected loads. It has a multi-tier user access that enables you to restrict unauthorized use of outlets. This rack has a single input power source making it easy to install.
Lead time	Usually in Stock

Main

Color	Black
Product or Component Type	PDU
PDU Type	Switched
Cord length	12 ft (3.7 m)
Number of cables	1
Provided Equipment Cord retention bracket(s) Horizontal mounting brackets User Manual Installation guide	

Complementary

Input Voltage	100 V 120 V
Height	1.73 in (4.4 cm)
Width	17.52 in (44.5 cm)
Output Voltage	120 V
Depth	4.25 in (10.8 cm)
Net Weight	5.004 lb(US) (2.27 kg)
Mounting Location	Front Rear
Mounting preference	No preference
Input Plug Type	NEMA 5-15P
Mounting Mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
Line Rated Current	12 A

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Acceptable Input Voltage	100120 V
Input current limits	15 A
Load Capacity	1440 VA
Input Frequency	50/60 Hz
Outlet type and quantity	8 NEMA 5-15R

Environment

Product Certifications	cUL Listed UL Listed
Standards	FCC Part 15 class A ICES-003
Ambient Air Temperature for Operation	32113 °F (045 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	095 %
Storage altitude	050000 ft (015240 m)

Ordering and shipping details

_	· · · · · ·
Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304331568
Returnability	No
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.76 in (7 cm)
Package 1 Width	13.50 in (34.3 cm)
Package 1 Length	18.50 in (47 cm)
Package 1 Weight	7.61 lb(US) (3.45 kg)

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	916
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
₩ Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	Yes

Product data sheet

AP7900B

Image of product / Alternate images

Alternative

