

Product data sheet

Specifications



ClimaSys PTC heating resistance 150W, 110-250V

NSYCR150WU2

Product availability: Stock - Normally stocked in distribution facility

Overview

Lead time	Usually Ships within 4 Weeks
-----------	------------------------------

Main

Range	ClimaSys
Product name	ClimaSys CR
Product or Component Type	Resistance heater
Power range	150 W
Input voltage	110...250 V AC 50/60 Hz

Complementary

Operating position	Vertical
Ambient air temperature for operation	-40...158 °F (-40...70 °C)
IP Degree of Protection	IP20
Product Certifications	VDE UL
Material	Body extruded aluminium
Height	11.2 in (285 mm)
Width	3.1 in (80 mm)
Depth	2.8 in (70 mm)
Condition of use	Heaters must be installed with a thermal controller Air sealed enclosure Electrical protection is needed
Fixing Mode	By clips
Mounting Support	35 mm DIN rail

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480152221
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Nbr. of units in pkg.	1
Package 1 Height	2.756 in (7.000 cm)
Package 1 Width	3.150 in (8.000 cm)
Package 1 Length	11.220 in (28.500 cm)
Package weight(Lbs)	28.395 oz (805.000 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	12
Package 2 Height	6.102 in (15.500 cm)
Package 2 Width	10.236 in (26.000 cm)
Package 2 Length	22.835 in (58.000 cm)
Package 2 Weight	23.281 lb(US) (10.560 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	360
Package 3 Height	47.244 in (120.000 cm)
Package 3 Width	31.496 in (80.000 cm)
Package 3 Length	47.244 in (120.000 cm)
Package 3 Weight	727.526 lb(US) (330.000 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	60bb7229-9ac3-41cb-896e-a93aa448ebf8
REACH Regulation	REACH Declaration

Use Again

 Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.