

Product data sheet

Specifications



Actassi - perforated tray - 1U - depth 800 mm

NSYBBF1U60P

Product availability: Stock - Normally stocked in distribution facility

Overview

Presentation	Power Management
Lead time	Usually Ships within 4 Weeks

Main

Range of Product	Actassi
Product or Component Type	Fixed perforated shelf
Accessory / separate part category	Support accessory
color	Gray RAL 7035)

Complementary

Range Compatibility	Actassi VDS Actassi VDA
Material	sheet steel
Mounting Location	Between the front and rear 19" uprights
Fixing mode	Direct fixing
Number of rack unit	1U
Adjustment	Adjustable from -100 to + 50 mm, in steps of 25 mm
Permanent permissible load	220.5 lb(US) (100 kg)
Distance between centers	18.03 in (458 mm)
Number of rack unit	29U 47U 42U 33U 38U 24U
Enclosure/cubicle description	Enclosure width: 600 mm depth: 31.5 in (800 mm) height: 47.2 in (1200 mm) Enclosure width: 800 mm depth: 31.5 in (800 mm) height: 47.2 in (1200 mm) Enclosure width: 600 mm depth: 31.5 in (800 mm) height: 55.1 in (1400 mm) Enclosure width: 800 mm depth: 31.5 in (800 mm) height: 55.1 in (1400 mm) Enclosure width: 600 mm depth: 31.5 in (800 mm) height: 63.0 in (1600 mm) Enclosure width: 800 mm depth: 31.5 in (800 mm) height: 63.0 in (1600 mm) Enclosure width: 600 mm depth: 31.5 in (800 mm) height: 70.9 in (1800 mm) Enclosure width: 800 mm depth: 31.5 in (800 mm) height: 70.9 in (1800 mm) Enclosure width: 600 mm depth: 31.5 in (800 mm) height: 78.7 in (2000 mm) Enclosure width: 800 mm depth: 31.5 in (800 mm) height: 78.7 in (2000 mm) Enclosure width: 600 mm depth: 31.5 in (800 mm) height: 86.6 in (2200 mm) Enclosure width: 800 mm depth: 31.5 in (800 mm) height: 86.6 in (2200 mm)
Depth	Rack : 23.6 in (600 mm)

Ordering and shipping details

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480172403
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.969 in (5.000 cm)
Package 1 Width	18.504 in (47.000 cm)
Package 1 Length	24.016 in (61.000 cm)
Package weight(Lbs)	9.326 lb(US) (4.230 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	32
Package 2 Height	29.528 in (75.000 cm)
Package 2 Width	31.496 in (80.000 cm)
Package 2 Length	48.031 in (122.000 cm)
Package 2 Weight	403.446 lb(US) (183.000 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	67feaae3-1a02-4290-bfbd-a29ec2a78217
REACH Regulation	REACH Declaration

Use Again

Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No