



APC Smart-UPS On-Line, 3kVA, Rackmount 2U, 120V, 8x 5-20R+1x L5-30R NEMA outlets, Network Card, Extended runtime, W/ rail kit

SRT3000RMXLA-NC

#### **Overview**

Presentation	High density, double-conversion on-line power protection with scalable runtime.	
Lead time	Usually in Stock	

Main	
Main Input Voltage	120 V AC 1 phase
Product or Component Type	Uninterruptible power supply (UPS)
Main Output Voltage	120 V 1 phase
Kw Rating	2700 W
Rated power in VA	3000 VA
Input Connection Type	NEMA L5-30P
output connection type	8 NEMA 5-20R 1 NEMA L5-30R
Number of rack unit	2U
Cable length	7.9 ft (2.4 m)
Number of cables	1
Provided equipment	CD with software Documentation CD Installation guide Network Management Card Rack Mounting brackets Rack Mounting support rails USB cable Warranty card
Range of Product	Smart-UPS On-Line

#### Complementary

Battery Size	Lead-acid internal
UPS connectivity	Serial port USB port Pre-installed network management card 3
Mounting mode	Rack-mounted with kit sold separately

#### **Batteries & Runtime**

Battery Type	Lead-Acid battery
Efficiency	View Efficiency Graph ☐
Run Time	View Runtime Graph ☐

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Battery Voltage	96V
Extendable Run Time	1
Included Battery Modules	1
Typical recharge time	3 h
RBC Quantity	1
Battery life	35 year(s)
Replacement battery	APCRBC152 ☐
Battery Charge Power (Watts)	151 W rated

## General

Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	High density
Redundant	No
Topology	Double Conversion Online

# **Physical**

color	Black
Height	3.3 in (85 mm)
Width	17.008 in (432 mm)
Depth	25 in (635 mm)
Net Weight	69.005 lb(US) (31.3 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal

## Input

Input Frequency 40 - 70 Hz auto-sensing

# Output

Bypass type	Internal Bypass (Automatic and Manual)	
Crest factor	3:1	
Harmonic distortion	Less than 2%	
Maximum configurable power in VA	3000 VA	
Max Configurable Power (Watts)	2700 W	
Waveform Type	Sine wave	
Output frequency	50/60 Hz +/- 3 Hz sync to mains	

## Conformance

Product Certifications ENERGY STAR V2.0 (USA)

#### **Environmental**

Acoustic level	55 dBA
Heat dissipation	805 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	32104 °F (040 °C)
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage altitude	050000 ft (015240 m)
IP degree of protection	IP20
Relative Humidity	095 % non-condensing
Storage Relative Humidity	095 % non-condensing

## **Communications & Management**

Emergency Power Off (EPO)	Yes
Free slots	0
Pre-Installed SmartSlot™ Cards	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity

## **Surge Protection and Filtering**

Surge energy rating 340 J

## Ordering and shipping details

GTIN 731304325178

## **Packing Units**

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	9.7 in (24.6 cm)
Package 1 Width	34.3 in (87.1 cm)
Package 1 Length	23.6 in (59.9 cm)
Package weight(Lbs)	88.009 lb(US) (39.92 kg)

## **Contractual warranty**

Warranty 3 years repair or replace (excluding battery) and 2 years for battery



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	8026
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Optimized Energy Efficiency	Energy efficient product
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## **Product data sheet**

# SRT3000RMXLA-NC

**Technical Illustration** 

**Dimensions** 



## **Product data sheet**

# SRT3000RMXLA-NC

Image of product / Alternate images

**Alternative** 

