

Product data sheet

Specifications



APC NetShelter Basic Rack PDU, Zero U, 20A, 120V, 14 NEMA 5-15 outlets

AP9551

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Color	Black
Product or Component Type	PDU
PDU Type	Basic
Cord length	11.98 ft (3.65 m)
Number of cables	1
Provided Equipment	Rack Mounting brackets Toolless Mounting Kit User Manual

Complementary

Input Voltage	100 V 120 V
Height	24.02 in (610 mm)
Width	1.7 in (42 mm)
Output Voltage	120 V
Depth	1.7 in (44 mm)
Net Weight	4.9 lb(US) (2.2 kg)
Mounting Location	Side
Mounting preference	No preference
Input Plug Type	NEMA L5-20P
Mounting Mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Line Rated Current	16 A
Acceptable Input Voltage	90...132 V
Max line current	20 A
Input current limits	20 A
Load Capacity	1920 VA
Input Frequency	50/60 Hz
Outlet type and quantity	14 NEMA 5-15R

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Product Certifications	cUL Listed CSA UL Listed
Ambient air temperature for operation	32...113 °F (0...45 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0...15240 m)

Ordering and shipping details

GTIN	731304021247
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	25.5 in (64.8 cm)
Package 1 Width	6.0 in (15.2 cm)
Package 1 Length	7.008 in (17.8 cm)
Package weight(Lbs)	6.44 lb(US) (2.92 kg)

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	1750
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration
Halogen content performance	Product contains halogen above thresholds

Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.