

# BEAM CLAMP, 1/4" ROD 1, #10 ROD 2, 1/2" MAX FLANGE

# **CATALOG NUMBER**

# BC



# **CERTIFICATIONS**





#### **FEATURES**

Easy installation to beam flanges

# PRODUCT ATTRIBUTES

Material: Spring Steel

Finish: nVent CADDY Armour


Rod Size 1: 1/4" Rod Size 2: #10 Hole Size: 10.5 mm

Flange Thickness: 16 mm max

Torque: 3 N·m Static Load: 440 N

# ADDITIONAL PRODUCT DETAILS

Setscrew must be tightened and torqued onto the sloped side of the I-beam.



#### WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

#### **North America**

+1.800.753.9221 Option 1 - Customer Care Option 2 - Technical Support Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404 **APAC** 

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN **SCHROFF** RAYCHEM

**TRACER** 

nVent.com