

BEAM CLAMP, 1/4" ROD 1, #10 ROD 2, 1/2" MAX FLANGE

CATALOG NUMBER

BC



CERTIFICATIONS



FEATURES


Easy installation to beam flanges

PRODUCT ATTRIBUTES

Material: Spring Steel
Finish: nVent CADDY Armour
Rod Size 1: 1/4"
Rod Size 2: 10"
Hole Size: 7/16"
Flange Thickness: 1/2" Max
Torque: 20"·lb
Static Load: 100 lb

ADDITIONAL PRODUCT DETAILS

Setscrew must be tightened and torqued onto the sloped side of the I-beam.



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands: **nVent.com** CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.